

TORO

Count on it.

Greensmaster® TriFlex™ & TriFlex Hybrid Greensmowers

F E A T U R E S

Advanced Cutting Performance

- Patent pending Double A-Arm Suspension for superior contour following
- Industry leading Flex technology and DPA cutting units for easy adjustment and precision
- Innovative Lift-In-Turn feature for a consistently level cleanup cut
- Enhanced clippings capture system for improved turf health

Highly Productive and Versatile

- Powerful 21hp Briggs & Stratton Vanguard Gasoline or 23hp Kubota Diesel engine
- Ample power for a wide range of applications both on and off the greens
- 10mph transport speed to save time and improve productivity

Innovative Maintenance Enhancements

- A Lift-Gate Footrest provides easy access to the center cutting unit for simplified maintenance and adjustments
- Tool-Free, Quick Change cutting units for greater versatility, simplified maintenance, and enhanced productivity
- Large, balloon-style tires ensure equal pressure on the turf to minimize tire marking and reduce scuffing in turns

All-Electric Reel Technology

(Hybrid models only)

- Custom designed, highly efficient electrical reel motors
- Electrical energy storage for peak power demands

Setting a new standard by which all other riding greensmowers will be measured.

The all-new Greensmaster TriFlex and TriFlex Hybrid models are the first riding greens mowers delivering the productivity of a rider and the precision of a walker. Combining the all-new, Double A-Arm Suspension System with industry-leading Flex technology, the cutting units float freely over any terrain resulting in a superior quality of cut and aftercut appearance. And, superior cutting performance is only the beginning. A patented Lift-Gate footrest and Tool-Free, Quick Change cutting units are just two of the many features that provide added versatility, simplified service, and ultimately, more productivity.

The TriFlex Hybrid models feature a reliable all-electric reel circuit that was custom designed with ample power for your most demanding applications, on and off the green.

Features that save time and energy, and enhance productivity and turf health combine to make the TriFlex Hybrid the first product to earn the EnergySmart™ label from Toro.


877.683.1032

sales | rentals | parts | service

nessturf.com

Greensmaster® TriFlex™ & TriFlex Hybrid Specifications*



	GREENSMAS TM TER 3300 TRIFLEX, MODEL 04510	GREENSMAS TM TER 3320 TRIFLEX HYBRID, MODEL 04530	GREENSMAS TM TER 3400 TRIFLEX, MODEL 04520	GREENSMAS TM TER 3420 TRIFLEX HYBRID, MODEL 04540
ENGINE	Briggs & Stratton® Vanguard®, 21 HP (13.4 kW), 2-cylinder, air cooled, gasoline engine, governed to 2920 high idle, 1650 rpm low idle. Displacement: 38.3 cu-in. (627 cc)		Kubota® D902, 23.5 HP (17.5 kW), 3-cylinder, liquid cooled, diesel engine, governed to 2880 high idle, 1560 rpm low idle. Displacement: 55.0 cu-in. (902 cc) Radiator: cooled with a 12-volt electric fan	
FUEL CAPACITY	6 gallons (22.7 liter) capacity.			
TRACTION DRIVE	2WD parallel hydrostatic or 3WD series-parallel piston pump closed loop system. Foot pedal forward and reverse; infinitely variable.			
GROUND SPEED	Forward-mowing speed is variable from 0-5 mph (0-8 km/h), adjusted by stop on pedal mechanism. Mow speed setting does not affect transport speed. Maximum Greensmaster TriFlex transport speed is 10 mph (16.1 km/h), may be reduced by adjusting stop in footrest pan without affecting mow speeds. Reverse is 3 mph (4.8 km/h) maximum.			
CUTTING UNIT DRIVE	Single gear pump, mono valve block, series reel drive to 3 reel motors.	48V-5400 watt air-cooled brushless permanent magnet generator in parallel with 48V 9Ah battery set powers three 48V- 1100 watt brushless permanent magnet reel motors.	Single gear pump, mono valve block, series reel drive to 3 reel motors.	48V-5400 watt air-cooled brushless permanent magnet generator in parallel with 48V 9Ah battery set powers three 48V- 1100 watt brushless permanent magnet reel motors.
STEERING	Power steering. No-tool quick adjust steering arm position, with arm motion allowing a wide range of operator sizes. Steering cylinder has a through shaft design for accurate straight line steering.			
ELECTRICAL SYSTEM	12-volt lead acid, group size U1, with 300 minimum cold cranking amps at 0° F and 34 minutes reserve capacity at 85° F/25 ampsdraw. 50 amp alternator. Ignition switch/key. Seat switch. Harness terminals and fuse slot available for optional lights installation.		Maintenance-free 12-volt battery with 585 minimum cold cranking amps at 0° F (-17.7° C) and 95 minutes minimum reserve capacity at 85° F (29.4° C) 60 amp alternator, circuit fused at 60 amps. Ignition switch/key. Seat switch. High temperature engine shut down. Harness terminals, fuse slot, and console switch location available for optional lights installation.	
48-VOLT SYSTEM FOR ELECTRIC REELS	N/A	4-12V 9Ah sealed, maintenance-free, VRLA batteries. 48-volt system is isolated from 12-volt including the frame/chassis.	N/A	4-12V 9Ah sealed, maintenance-free, VRLA batteries. 48-volt system is isolated from 12-volt including the frame/chassis.
CONTROLS	Ignition: Off/Run/Start. Throttle: Low - High Idle. Choke (AC only): Open /Closes choke plate. Parking Brake: Off - On. Traction Pedal: Rev/Neutral/Forward Joystick: Raises/lowers reels also tap off feature for clean up pass. Functional Control Lever sets neutral/mow/transport limits for traction pedal. Diagnostic Light: Indicates system faults to assist in resolving issues.			
GAUGES	Fuel and hydraulic sight gauges, hour meter. Low oil pressure warning light.	Fuel and hydraulic sight gauges, hour meter. Low oil pressure warning light.	Fuel and hydraulic sight gauges, hour meter. Low oil pressure warning light, alternator warning light (on if not charging), glow plug indicator, high engine temperature.	Fuel and hydraulic sight gauges, hour meter. Low oil pressure warning light, alternator warning light (on if not charging), glow plug indicator, high engine temperature.
TIRES/WHEELS/PRESSURE	Three, 19 x 10.5 x 8, 4-ply rating pneumatic tubeless demountable. Smooth tread. Tire pressure recommended: 12 - 18 psi front and rear.			
BRAKES	Hand-actuated parking brake lever with two 6" (15.2 cm) diameter drum brakes mounted on the front wheel motors.			
HYDRAULIC OIL	6.8 gallon (25.7 liter) tank	5.5 gallon (20.8 liter) tank	6.8 gallon (25.7 liter) tank	5.5 gallon (20.8 liter) tank
LEAK DETECTION	Equipped with Turf Guardian™ Leak Detection System. System sounds an alarm and turns on a warning light with the loss of 3 to 5 ounces of hydraulic oil.	Optional		
SOUND LEVEL	80 dB(A) at operator's ear under normal conditions.		84 dB(A) at operator's ear under normal conditions.	
OVERALL DIMENSIONS	Wheel Tread: 50.5" (128.3 cm) Wheel Base: 47" (119 cm) Length: 98" (249 cm) Width: 70.62" (179 cm) w/reels Height: 80.83" (205 cm)	Wheel Tread: 50.5" (128.3 cm) Wheel Base: 47" (119 cm) Length: 98" (249 cm) Width: 70.84" (180 cm) w/reels Height: 80.83" (205 cm)	Wheel Tread: 50.5" (128.3 cm) Wheel Base: 48.6" (123 cm) Length: 98" (249 cm) Width: 70.62" (179 cm) w/reels Height: 80.83" (205 cm)	Wheel Tread: 50.5" (128.3 cm) Wheel Base: 48.6" (123 cm) Length: 98" (249 cm) Width: 70.84" (180 cm) w/reels Height: 80.83" (205 cm)
WEIGHT	1161 lbs. (526 kg)	1257 lbs. (570 kg)	1286 lbs. (586 kg)	1406 lbs. (638 kg)
WIDTH OF CUT	59" (150 cm)			
GROUND CLEARANCE	4.5" (11.4 cm)			
CUTTING UNIT SUSPENSION	Double A-arm suspension utilizing sealed ball joints allows free cutting unit motion in pitch, roll, and yaw. The basket is directly mounted to the cutting unit displacing weight evenly over both cutting unit rollers eliminating the carrier frame, roller and pull links.			
QUICK CONNECT CUTTING UNITS	Quick connect/disconnect feature for both the reel drive motor and cutting unit. No tools required.			
REEL SPEED	Approximately 2050 RPM at 2850 engine RPM. Adjustable.			
BACKLAPPING	Standard equipment.			
OPTIONAL ACCESSORIES	Canopy, verticutters, greens rollers, dethatchers, dew whip holder, oil cooler.			
CERTIFICATION	Certified to meet ANSI specification B71.4 - 2004 and European CE standards.			
WARRANTY	Two-year limited warranty. Refer to the Operator's Manual for further details.			

*Specifications and design subject to change without notice.

Greensmaster® TriFlex™ & TriFlex Hybrid Specifications*



	8-BLADE DPA CUTTING UNITS, 04613	11-BLADE DPA CUTTING UNITS, 04614	14-BLADE CUTTING UNITS, 04615
TRACTOR	These cutting units will mount on the Greensmaster 3XXX series.		
HEIGHT OF CUT (HOC) RANGE	Cutting height is adjusted on front roller by two vertical screws and held by two locking cap screws. Bench HOC range is .062"-.297" (1.6-7.5 mm). With high HOC kit, range is .285-1" (7.3-25.4 mm). Effective HOC may vary depending on turf conditions and bedknife installed.		
REEL WELDMENT	Reels are 5" (13 cm) in diameter, 21" (53.3 cm) in length. High carbon steel blades are welded to 5 stamped steel spiders, and heat treated to RC 48-54 hardness. The reel is ground for diameter and concentricity, and backgrind.		
REEL BEARINGS	Two stainless steel ball bearings, 30 +/- .1 mm inside diameter slip fit onto reel shaft retained by internally splined threaded insert. Low drag seals/slingers for added protection with o-ring sealed motor and counterweight. Reel position maintained by a wave washer with no adjusting nut.		
MAINTENANCE	No grease zerks, sealed bearing design eliminates daily maintenance.		
REEL DRIVE	The reel weldment shaft is a 1.375" (35 mm) diameter tube with internally splined threaded insert.		
FRAME	Precision machined, die-cast aluminum cross member with two bolt-on die-cast aluminum side plates.		
AGGRESSIVENESS	Aggressiveness stays constant throughout the life of the reel. Patented design.		
BEDKNIFE	Replaceable single edged, high carbon steel bedknife austempered to RC 55-58, fastened to a machined cast iron bedbar with 13 screws. EdgeMax™ Microcut Bedknife is standard on all cutting units.		
BEDKNIFE ADJUSTMENT	Dual screw, indexed "click" adjustment to the reel; detents corresponding positively to .0007" (.018 mm) bedknife movement for each position.		
FRONT & REAR ROLLERS	Front: Aluminum Wiehle®, 2.5" (6.4 cm) diameter with sealed bearings and through-shaft. Option between full, narrow-spaced and wide-spaced roller. Rear: Steel full, 2" (5.1 cm) diameter with sealed bearings and through-shaft.		
GRASS SHIELD	Non-adjustable shield with adjustable cut-off bar to improve grass discharge from reel in wet conditions.		
TOTAL WEIGHT	8-blade: 80 lbs. (30.4 kg) with aluminum Wiehle Roller. 11-blade: 83 lbs. (37.7 kg) with aluminum Wiehle Roller. 14-blade: 86 lbs. (39 kg) with aluminum Wiehle Roller.		

GREENSMASTER TRIFLEX ACCESSORIES

TRIFLEX TRACTION UNIT ACCESSORIES	
04714	3WD Kit
04715	Leak Detector
04717	Light Kit
04718	Seat Kit, Standard
04719	Seat Kit, Premium
92-7307	Armrest Kit - Standard
119-7105	Armrest Kit - Premium
119-1691	Hydraulic Oil Cooler Kit:Gas
117-9314	Hydraulic Oil Cooler Kit: Diesel
119-7129	2WD Weight Kit (ANSI compliance)
120-5750	3WD Weight Kit (ANSI compliance)
104-6540	Spark Arrestor Kit (Gas)
120-1951	Spark Arrestor Kit (Diesel)
119-7138	Dew Whip Holder
115-4510	Canopy
119-1715	Utility Bag Kit

TRIFLEX DPA CUTTING UNITS	
04613	8-Blade Cutting Unit
04614	11-Blade Cutting Unit
04615	14-Blade Cutting Unit

TRIFLEX DPA CUTTING UNIT ROLLERS	
04625	Full Roller DPA
04626	Narrow Wiehle Roller DPA
04627	Wide Wiehle Roller DPA
04628	Solid Steel Roller Kit (Front Wide Wiehle, Rear Full)
04629	Anti Bobbing Roller - DPA (Front and Rear)
107-9561	Anti Bobbing Roller - Scraper Kit (Front and Rear)
114-4630	DPA Rear Roller Adjustment Kit
71-1550	2" Rear Wiehle Roller (cast iron)
112-9294	Rear Roller Extension Kit
TBD	High Height of Cut Kit (.35 - .94)

TRIFLEX DPA CUTTING UNIT ACCESSORIES	
04710	Groomer Drive
04711	Groomer Reel, Carbide
04712	Groomer Reel, Spring Steel
04713	Groomer Brush
04724	Rotating Rear Roller Brush
115-1880	EdgeMax Microcut Bedknife
115-1881	EdgeMax Tournament Bedknife
93-4262	Microcut Bedknife (HOC Range 1.58mm - 3.18mm)
93-4263	Tournament Bedknife (HOC Range 0.32mm - 6.35mm)
93-4264	Low Cut Bedknife (HOC Range 6.35mm and higher)
94-6392	Bedknife - High Cut
108-4303	Extended Microcut Bedknife
108-4302	Extended Tournament Bedknife
63-8600	Bedknife - Fairway
99-3794-03	DPA Bedbar (aggressive - optional)
106-2648-01	DPA Bedbar (less aggressive - standard equipment)

*Specifications and design subject to change without notice.

Greensmaster® TriFlex™ & TriFlex Hybrid Accessories*



GREENSMaster TRIFLEX ACCESSORIES

TRIFLEX DPA CUTTING UNIT ROLLER SCRAPER / BRUSHES / COMBS	
04725	Rear Roller Scraper
108-6468	Front Wiehle Roller Scraper - Narrow
110-3961	Front Wiehle Roller Scraper - Wide
110-3962	Front Roller Scraper - Full
115-7377	Front Wiehle Roller Scraper Brush - Narrow
115-7378	Front Wiehle Roller Scraper Brush - Wide
115-7379	Front Roller Scraper Brush - Full
110-3966	Front Wiehle Roller Scraper Comb - Narrow
110-3967	Front Wiehle Roller Scraper Comb - Wide
110-3968	Front Roller Scraper Comb - Full
112-9353	Rear Roller Scraper - Adjustable

OPTIONAL TRIFLEX ACCESSORIES	
04720	Thatching Reel Kit - TriFlex
119-1128	Individual dynaBLADE, 2mm thickness
117-6824	Individual dynaBLADE, 1.2mm thickness
117-6839	Replacement dynaBLADE kit, 1.2mm thickness (36 blades)
117-6840	Replacement dynaBLADE kit, 2mm thickness (36 blades)
95-5943	Thatching Reel - Rear Roller
95-1600	Thatching Rear Roller Scraper for 95-5943
TBD	Greens Tri-Roller Kit - TriFlex
TBD	Greens Spiker Kit - TriFlex

TRIFLEX SERVICE KITS	
30042	400 hour filter Maintenance Kit - Greensmaster TriFlex 3300/3320
30043	400 hour filter Maintenance Kit - Greensmaster TriFlex 3400/3420